# TRAIL LINK

MANUFACTURER AND SUPPLIER OF TRAILER CONNECTORS AND ACCESSORIES




#### How to differentiate the BEST from the rest

## IT IS TRAILLINK® when...









**Certificate of Authenticity** 

**Proudly South African** 





**Functional bend restrictors** 

Trail-Link printed on moulded plugs



Remember RALLINK doesn't fail.

DESCRIPTION PAGE

TRAIL-LINK BACKGROUND
SECTION 1: ELECTRICAL SUZIS
Electrical Suzis - Products 4 - 11
SECTION 2: CONSTANT POWER BRAKING COILS 12
Constant Power Braking Coils - Products13
SECTION 3: PLUGS
Plugs - Products
SECTION 4: SOCKETS
Sockets - Products 19 - 23
SECTION 5: HIGH AMP RATING/MILITARY (NATO) SPEC
High Amp Rating - Products
Military (NATO) Spec - Products
Pole (NATO) Spec - Products
SECTIONS 6: ANTI-KINK AIR COILS
Anti-Kink Air Coils - Products
SECTION 7: ACCESSORIES
Accessories - Products
SECTION 8: LED LIGHT RANGE
LED Light Range - Products
SECTION 9: UNDERBODY ACCESSORIES
Underbody Accessories - Products47 - 50
SECTION 10: LATEST CONCEPTS
Latest Concepts - Products

#### BACKGROUND

Trail-Link is a family operated business established in 2004 when the members started developing products based on previous experience in the transport industry.

Trail-Link's product range started with the development of a high quality electrical suzi with moulded plugs and a universal catch assembly providing LOCK-IN of these connectors.

The range has since expanded due to industry demand to include plugs, sockets, harnesses and accessories which are now fitted as standard on leading OE brands.

Trail-Link's mission is to offer solutions for all electrical connector requirements. Our vision is to continue to do so.

Trail-Link is a registered Proudly South African company





## SECTION 1 ELECTRICAL SUZIS

Trail-Link's electrical suzis are produced from high quality polyurethane, selected for its unbeatable wear-and-tear properties.

Our coils are weather, oil, grease, abrasion and UV resistant and have excellent recoil memory to reduce sag.


The impact resistant plugs are wired to their correct standard and are tested in production.

Our electrical suzis offer the ideal PLUG-IN & GO solution for any horse/trailer combination. The working lengths of the suzis range from 1.7m to 4.5m depending on the product.

#### **SECTION 1: ELECTRICAL SUZIS**

#### NEW STYLE POLY-U SUZI WITH TWO MOULDED PLUGS - PART # 101-203





SOUTH AFRICAN STANDARD					
CONTACT/FUNCTION	COLOUR	NO.			
Left turn/Hazard	Yellow	1			
Spare	Blue	2			
Earth/Return/Ground	White	3			
Right turn/Hazard	Green	4			
Right tail/Number plate	Brown	5			
Stop	Red	6			
Left tail/Number plate	Black	7			

#### **FEATURES**

- Polyurethane coil
- · Functional bend restrictor
- 2 x Moulded plugs
- Wire sizes: 6 x 1.0 mm<sup>2</sup> + 1 x 1.5 mm<sup>2</sup>
- Working length: ± 3.5 m
- Light weight coil offering exceptional performance

#### ALL DUTY POLY-U SUZI WITH TWO MOULDED PLUGS - PART # 100-203



7 PIN


SOUTH AFRICAN STANDARD					
CONTACT/FUNCTION	COLOUR	NO.			
Left turn/Hazard	Yellow	1			
Spare	Blue	2			
Earth/Return/Ground	White	3			
Right turn/Hazard	Green	4			
Right tail/Number plate	Brown	5			
Stop	Red	6			
Left tail/Number plate	Black	7			

- Polyurethane coil
- Functional bend restrictor
- 2 x Moulded plugs

- Wire sizes: 6 x 1.5 mm<sup>2</sup> + 1 x 2.5 mm<sup>2</sup>
- Working length: ± 3.5 m

#### ALL DUTY POLY-U SUZI WITH MOULDED PLUG (SINGLE END) - PART # 100-204






SOUTH AFRICAN STANDARD					
CONTACT/FUNCTION	COLOUR	NO.			
Left turn/Hazard	Yellow	1			
Spare	Blue	2			
Earth/Return/Ground	White	3			
Right turn/Hazard	Green	4			
Right tail/Number plate	Brown	5			
Stop	Red	6			
Left tail/Number plate	Black	7			

- Polyurethane coil
- · Functional bend restrictor
- 1 x Moulded plug

- 1 x End free for hard-wiring applications
- Wire sizes: 6 x 1.5 mm<sup>2</sup> + 1 x 2.5 mm<sup>2</sup>
- Working length: ± 3.5 m

#### LONG TAIL POLY-U SUZI WITH TWO MOULDED PLUGS - PART # 100-503





SOUTH AFRICAN	STANDAR	D
CONTACT/FUNCTION	COLOUR	NO.
Left turn/Hazard	Yellow	1
Spare	Blue	2
Earth/Return/Ground	White	3
Right turn/Hazard	Green	4
Right tail/Number plate	Brown	5
Stop	Red	6
Left tail/Number plate	Black	7


- Polyurethane coil
- · Functional bend restrictor
- · 2 x Moulded plugs

- Wire sizes: 6 x 1.5 mm<sup>2</sup> + 1 x 2.5 mm<sup>2</sup>
- Working length: ± 4.5 m
- 1 m long tail for extended reach

#### **SECTION 1: ELECTRICAL SUZIS**

#### LONG TAIL POLY-U SUZI WITH MOULDED PLUG - PART # 100-504





SOUTH AFRICAN STANDARD					
CONTACT/FUNCTION	COLOUR	NO.			
Left turn/Hazard	Yellow	1			
Spare	Blue	2			
Earth/Return/Ground	White	3			
Right turn/Hazard	Green	4			
Right tail/Number plate	Brown	5			
Stop	Red	6			
Left tail/Number plate	Black	7			

#### **FEATURES**

- Polyurethane coil
- Functional bend restrictor
- 1 x Moulded plug
- 1 x End free for hard-wiring applications
- Wire sizes: 6 x 1.5 mm<sup>2</sup> + 1 x 2.5 mm<sup>2</sup>
- Working length: ± 4.5 m
- 1 m long tail for extended reach

#### EURO/USA TO SA ADAPTER SUZI - PART # 100-403



7 PIN EURO/USA

±3.5 m

7 PIN


EUROPEAN STANDARD		SOUTH AFRICAN	STANDAR	D		
	CONTACT/FUNCTION	COLOUR	NO.	CONTACT/FUNCTION	COLOUR	NO.
	Earth/Return/Ground	White	1	Earth/Return/Ground	White	3
	Left tail/Number plate	Black	2	Left tail/Number plate	Black	7
	Left turn/Hazard	Hazard Yellow 3		Left turn/Hazard	Yellow	1
	Stop	Red	4	Stop	Red	6
	Right turn/Hazard	Green	5	Right turn/Hazard	Green	4
	Right tail/Number plate	Brown	6	Right tail/Number plate	Brown	5
	Trailer brake control	Blue	7	Spare	Blue	2

- Polyurethane coil
- Functional bend restrictor
- 1 x SA moulded plug
- 1 x EURO/USA moulded plug

- · Plugs wired to correct standard
- Wire sizes: 6 x 1.5 mm<sup>2</sup> + 1 x 2.5 mm<sup>2</sup>
- Working length: ± 3.5 m
- Adapts from EURO style 7 Pin (Scania, DAF, MAN etc.) to SA style 7 Pin

#### 15 PIN TO 7 PIN ADAPTER SUZI - PART # 100-303





15 PIN EUROPEAN STANDARD			SOUTH AFRICAN	STANDAR	D
CONTACT/FUNCTION	COLOUR	NO.	CONTACT/FUNCTION	COLOUR	NO.
Left turn/Hazard	Yellow	1	Left turn/Hazard	Yellow	1
Right turn/Hazard	Green	2	Right turn/Hazard	Green	4
Fog tail light	Blue	3	Spare	Blue	2
Ground/Earth/Return for contacts 1-7	White	4	Ground/Earth/Return	White	3
Left tail/Number plate/Markers	Black	5	Left tail/Number plate	Black	7
Right tail/Number plate/Markers	Brown	6	Right tail/Number plate	Brown	5
Stop	Red	7	Stop	Red	6

#### **FEATURES**

- · Polyurethane coil
- · Functional bend restrictor
- 1 x SA moulded plug
- 1 x 15 Pin moulded plug (1-7 only)
- · Plugs wired to correct standard
- Wire sizes: 6 x 1.5 mm<sup>2</sup> + 1 x 2.5 mm<sup>2</sup>
- Working length: ± 3.5 m
- Adapts from EURO style 15 Pin (Mercedes, Volvo etc.) to SA style 7 Pin

#### NEW STYLE 15 PIN TO 7 PIN ADAPTER SUZI - PART # 101-303



15 PIN		7 PIN
	±3.5 m	000
<b>400</b>		

15 PIN EUROPEAN STANDARD		SOUTH AFRICAN	STANDAR	D	
CONTACT/FUNCTION	COLOUR NO. CONTACT/FUNCTION		COLOUR	NO.	
Left turn/Hazard	Yellow	1	Left turn/Hazard	Yellow	1
Right turn/Hazard	Green	2	Right turn/Hazard	Green	4
Fog tail light	Blue	3	Spare	Blue	2
Ground/Earth/Return for contacts 1-7	White	4	Ground/Earth/Return	White	3
Left tail/Number plate/Markers	Black	5	Left tail/Number plate	Black	7
Right tail/Number plate/Markers	Brown	6	Right tail/Number plate	Brown	5
Stop	Red	7	Stop	Red	6


- · Polyurethane coil
- · Functional bend restrictor
- 1 x SA moulded plug
- 1 x 15 Pin moulded plug (1-7 only)
- · Plugs wired to correct standard
- Wire sizes: 6 x 1.0 mm<sup>2</sup> + 1 x 1.5 mm<sup>2</sup>
- Working length: ± 3.5 m
- Volvo OE spec adapter

#### **SECTION 1: ELECTRICAL SUZIS**

#### POLY-U SUZI WITH TWO EURO MOULDED PLUGS - PART # 100-206



#### 7 PIN EURO/USA 7 PIN EURO/USA



EUROPEAN STANDARD					
CONTACT/FUNCTION	COLOUR	NO.			
Earth/Return/Ground	White	1			
Left tail/Number plate	Black	2			
Left turn/Hazard	Yellow	3			
Stop	Red	4			
Right turn/Hazard	Green	5			
Right tail/Number plate	Brown	6			
Trailer brake control	Blue	7			

#### **FEATURES**

- · Polyurethane coil
- · Functional bend restrictor
- 2 x EURO moulded plugs

- Wire sizes: 6 x 1.0 mm<sup>2</sup> + 1 x 1.5 mm<sup>2</sup>
- Working length: ± 3.5 m

#### POLY-U SUZI WITH TWO SUPPLEMENTARY MOULDED PLUGS - PART # 100-206SP



- · Polyurethane coil
- 2 x EURO supplementary moulded plugs with inverted pin
- Wire sizes: 6 x 1.0 mm<sup>2</sup> + 1 x 1.5 mm<sup>2</sup>
- Working length: ± 3.5 m

#### 15PIN TO EUROPEAN 7PIN ADAPTER SUZI - PART # 100-415

## 7 PIN EURO/USA 15 PIN

	EUROPEAN STANDARD		15 PIN EUROPEAN	I STANDA	RD	
	CONTACT/FUNCTION	T/FUNCTION COLOUR NO. CONTACT/FUNCTION		COLOUR	NO.	
	Earth/Return/Ground	White	1	Ground/Earth/Return for contact 1-7	White	4
	Left tail/Number plate	Black	2	Left tail/Number plate/Markers	Black	5
	Left turn/Hazard	Yellow	3	Left turn/Hazard	Yellow	1
	Stop	Red	4	Stop	Red	7
	Right turn/Hazard	Green	5	Right turn/Hazard	Green	2
	Right tail/Number plate	Brown	6	Right tail/Number plate/Markers	Brown	6
	Trailer brake control	Blue	7	Fog tail light	Blue	3

#### **FEATURES**


- Polyurethane coil
- Functional bend restrictor
- 1 x 7 Pin Euro moulded plug
- 1 x 15 Pin moulded plug (1-7 only)

- Plugs wired to correct standard
- Wire sizes: 6 x 1.5 mm<sup>2</sup> + 1 x 2.5 mm<sup>2</sup>
- Woking length = +/- 3.5m
- Adapts from Euro style 15 Pin to Euro style 7 Pin

#### 15 PIN POLY-U POWERCOIL COMPLETE - PART # 100-803




- LATORIES
- Polyurethane 15 Core coil
- Functional bend restrictor
- 2 x 15 Pin moulded plugs
- Wire sizes: 12 x 1.5 mm<sup>2</sup> + 3 x 2.5 mm<sup>2</sup>
- Working length: ± 3.5 m
- 15 functions



15 PIN EUROPEAN STAN	IDARD	
CONTACT/FUNCTION	COLOUR	NO.
Left turn/Hazard	Yellow	1
Right turn/Hazard	Green	2
Fog tail light	Blue	3
Ground/Earth/Return for contact 1-7	White	4
Left tail/Number plate/Markers	Black	5
Right tail/Number plate/Markers	Brown	6
Stop	Red	7
Reversing lights	Pink	8
Power supply (Continuous plus)	Orange	9
Brake lining wear sensor	Grey	10
Pressure sensor for spring brake system	White/Black	11
Rear axle lift system	White/Blue	12
Ground/Earth/Return for data line	White/Red	13
Data line	White/Green	14
Data IIIIe	White/Brown	15

#### NEW STYLE POLY-U SUZI WITH TWO 15 PIN PLUGS (1-7 ONLY) - PART # 101-800





15 PIN EUROPEAN STANDARD			
CONTACT/FUNCTION	COLOUR	NO.	
Left turn/Hazard	Yellow	1	
Right turn/Hazard	Green	2	
Fog tail light	Blue	3	
Ground/Earth/Return for contact 1-7	White	4	
Left tail/Number plate/Markers	Black	5	
Right tail/Number plate/Markers	Brown	6	
Stop	Red	7	


#### **FEATURES**

- · Polyurethane coil
- · Functional bend restrictor
- 2 x 15 Pin moulded plugs

- Wire sizes: 6 x 1.0 mm<sup>2</sup> + 1 x 1.5 mm<sup>2</sup>
- Working length: ± 3.5 m
- 7 primary functions

#### TRAIL-LINK 10 PIN COIL - PART # 100-803-10P





15 PIN STANDARD - 1 TO 10			
CONTACT/FUNCTION	COLOUR	NO.	
Left turn/Hazard	Yellow	1	
Right turn/Hazard	Green	2	
Fog tail light	Blue	3	
Ground/Earth/Return for contact 1-7	White	4	
Left tail/Number plate/Markers	Black	5	
Right tail/Number plate/Markers	Brown	6	
Stop	Red	7	
Reversing lights	Pink	8	
Power supply (Continuous plus)	Orange	9	
Brake lining wear sensor	Grey	10	

- · Polyurethane coil
- Functional bend restrictor
- 2 x 10 Pin moulded plugs (registered design)
- Working length: ± 3.5m

- Fully compatible with 15 Pin system
- Uses only 10 functions required in South Africa
- Less copper = more cost effective

### NEW STYLE 15 PIN (10 PIN DESIGN) TO 7 PIN ADAPTER SUZI WITH REVERSE FUNCTION - PART # 101-303-R



10 PIN
~

±3.5 m



15 PIN EUROPEAN STANDARD		SOUTH AFRICAN STANDARD			
CONTACT/FUNCTION	COLOUR	NO.	CONTACT/FUNCTION	COLOUR	NO.
Left turn/Hazard	Yellow	1	Left turn/Hazard	Yellow	1
Right turn/Hazard	Green	2	Right turn/Hazard	Green	4
Ground/Earth/Return for contact 1-7	White	4	Earth/Return/Ground	White	3
Left tail/Number plate/ Markers	Black	5	Left tail/ Number plate	Black	7
Right tail/Number plate/ Markers	Brown	6	Right tail/ Number plate	Brown	5
Stop	Red	7	Stop	Red	6
Reversing lights	Pink	8	Spare	Blue	2


#### **FEATURES**

- Polyurethane coil
- · Functional bend restrictor
- 1 x 10 Pin moulded plug (registered design)
- 1 x SA moulded plug

- Wire sizes: 6 x 1.0 mm<sup>2</sup> + 1 x 1.5 mm<sup>2</sup>
- Working length =  $\pm 3.5$ m
- · Fully compatible with 15 Pin system
- Reverse wired on spare (blue) line

#### MINI COIL WITH TWO MOULDED PLUGS - PART # 100-703





SOUTH AFRICAN STANDARD			
CONTACT/FUNCTION	COLOUR	NO.	
Left turn/Hazard	Yellow	1	
Spare	Blue	2	
Earth/Return/Ground	White	3	
Right turn/Hazard	Green	4	
Right tail/Number plate	Brown	5	
Stop	Red	6	
Left tail/Number plate	Black	7	

- Polvurethane coil
- Functional bend restrictor
- · 2 x Moulded plugs

- Wire sizes: 6 x 1.0 mm<sup>2</sup> + 1 x 1.5 mm<sup>2</sup>
- Working length: ± 1.7 m
- · Light duty / recreational applications

# SECTION 2 CONSTANT POWER BRAKING COILS

Trail-Link's Constant Power Braking Coils are produced from high quality polyurethane, selected for its unbeatable wear-and-tear properties. Our coils are weather, oil, grease, abrasion & UV resistant and offer excellent recoil memory.

ABS braking systems are now required by law on all new trailers – these coils come complete with the standard ABS/EBS plug & catch combination, and provide constant power from horse to trailer ensuring compliance.

#### **SECTION 2: CONSTANT POWER BRAKING COILS**

#### 7 PIN EBS/ABS BRAKING COIL COMPLETE - PART # 100-903





EBS		
CONTACT/FUNCTION	COLOUR	NO.
Solenoid control valve plus	Red	1
Electronic plus	Black	2
Electronic minus	Yellow	3
Solenoid control valve minus	Brown	4
Warning system	White	5
Data line	White/Green	6
Data IIIIE	White/Brown	7

#### **FEATURES**

- Polyurethane coil
- · Functional bend restrictor
- 2 x 7 Pin EBS moulded plugs
- Wire sizes: 5 x 1.5 mm<sup>2</sup> + 2 x 4 mm<sup>2</sup>
- Includes 2 x CAN data lines
- For ABS and EBS applications

#### SHORT REACH 7 PIN EBS/ABS BRAKING COIL COMPLETE- PART # 101-903





EBS		
CONTACT/FUNCTION	COLOUR	NO.
Solenoid control valve plus	Red	1
Electronic plus	Black	2
Electronic minus	Yellow	3
Solenoid control valve minus	Brown	4
Warning system	White	5
Data line	White/Green	6
Data lille	White/Brown	7

- · Polyurethane coil
- · Functional bend restrictor
- 2 x 7 Pin EBS moulded plugs
- Wire sizes: 5 x 1.5 mm<sup>2</sup> + 2 x 4 mm<sup>2</sup>
- Short reach for applications with reduced swing ideal for underslung use behind 5th wheel
- Includes 2 x CAN data lines
- · For ABS and EBS applications

# SECTION 3 PLUGS

Trail-Link's plugs are all supplied with correct pin position guidelines to ensure standard wiring and hassle-free connecting.

We provide u-connect versions of all the different plug standards used in South Africa.



#### U-CONNECT HIGH IMPACT TRAILER PLUG - PART # 500-102





SOUTH AFRICAN STANDARD		
CONTACT/FUNCTION	COLOUR	NO.
Left turn/Hazard	Yellow	1
Spare	Blue	2
Earth/Return/Ground	White	3
Right turn/Hazard	Green	4
Right tail/Number plate	Brown	5
Stop	Red	6
Left tail/Number plate	Black	7

#### **FEATURES**

- SA standard 7 Pin plug
- · High quality, non-conductive plastic body

#### 15 PIN PLUG - PART # 500-202



- 15 Pin plug for latest generation European vehicles
- Available with crimp type contacts (OE spec) or screw type contacts



15 PIN EUROPEAN STAN	IDARD	
CONTACT/FUNCTION	COLOUR	NO.
Left turn/Hazard	Yellow	1
Right turn/Hazard	Green	2
Fog tail light	Blue	3
Ground/Earth/Return for contact 1-7	White	4
Left tail/Number plate/Markers	Black	5
Right tail/Number plate/Markers	Brown	6
Stop	Red	7
Reversing lights	Pink	8
Power supply (Continuous plus)	Orange	9
Brake lining wear sensor	Grey	10
Pressure sensor for spring brake system	White/Black	11
Rear axle lift system	White/Blue	12
Ground/Earth/Return for data line	White/Red	13
Data line	White/Green	14
Data iiile	White/Brown	15

#### 7 PIN EBS PLUG - PART # 500-402





EBS		
CONTACT/FUNCTION	COLOUR	NO.
Solenoid control valve plus	Red	1
Electronic plus	Black	2
Electronic minus	Yellow	3
Solenoid control valve minus	Brown	4
Warning system	White	5
Data line	White/Green	6
Data line	White/Brown	7

#### **FEATURES**

- 7 Pin plug for EBS braking systems
- Can also be used on 5 Pin applications
- Available with crimp type contacts (OE spec) or screw type contacts

#### 7 PIN ALL MALE TRAILER PLUG - PART # 500-103



7 PIN (ALL MALE)



- Standard SA 7 Pin plug with all male pin configuration
- · High quality, non-conductive plastic body

#### EURO/USA METAL PLUG - PART # 500-302



#### 7 PIN EURO/USA



<b>EUROPEAN STANDARD</b>			
CONTACT/FUNCTION	COLOUR	NO.	
Earth/Return/Ground	White	1	
Left tail/Number plate	Black	2	
Left turn/Hazard	Yellow	3	
Stop	Red	4	
Right turn/Hazard	Green	5	
Right tail/Number plate	Brown	6	
Trailer brake control	Blue	7	

#### **FEATURES**

- 7 Pin EURO/USA standard plug
- · Heavy duty metal body

#### 13 PIN PLUG - PART # 500-902



- 13 Pin European 12 V standard plug
- Non-conductive plastic body
- Twist / Lock connection



13 PIN EUROPEAN STANDARD		
CONTACT/FUNCTION	COLOUR	NO.
Left turn/Hazard	Yellow	1
Fog tail light	Blue	2
Ground/Earth/Return for contact 1-7	White	3
Right turn/Hazard	Green	4
Right tail/Number plate/Markers	Brown	5
Stop	Red	6
Left tail/Number plate/Markers	Black	7
Reversing lights	Pink	8
Power supply (Continuous plus)	Orange	9
Power supply (Circuited with ignition switch)	Grey	10
Ground for power supply (Circuited with ignition switch)	White/Black	11
NOT OCCUPIED		12
Ground lead for reversing light and power supply (Continuous plus)	White/Red	13

## **SECTION 4 SOCKETS**

Trail-Link socket kits are supplied with the correct fasteners and wiring guidelines to ensure hassle free connecting.

#### U-CONNECT HIGH IMPACT TRAILER SOCKET - PART # 600-102



#### 7 PIN SOCKET



SOUTH AFRICAN STANDARD		
CONTACT/FUNCTION	COLOUR	NO.
Left turn/Hazard	Yellow	1
Spare	Blue	2
Earth/Return/Ground	White	3
Right turn/Hazard	Green	4
Right tail/Number plate	Brown	5
Stop	Red	6
Left tail/Number plate	Black	7

#### **FEATURES**

- SA standard 7 Pin socket
- · High quality, non-conductive plastic body

#### 15 PIN SOCKET - PART # 600-202



#### **FEATURES**

- 15 Pin socket for latest generation European vehicles
- Available with crimp type contacts (OE spec) or screw type contacts

#### 15 PIN SOCKET



15 PIN EUROPEAN STANDARD		
CONTACT/FUNCTION	COLOUR	NO.
Left turn/Hazard	Yellow	1
Right turn/Hazard	Green	2
Fog tail light	Blue	3
Ground/Earth/Return for contact 1-7	White	4
Left tail/Number plate/Markers	Black	5
Right tail/Number plate/Markers	Brown	6
Stop	Red	7
Reversing lights	Pink	8
Power supply (Continuous plus)	Orange	9
Brake lining wear sensor	Grey	10
Pressure sensor for spring brake system	White/Black	11
Rear axle lift system	White/Blue	12
Ground/Earth/Return for data line	White/Red	13
Data line	White/Green	14
	White/Brown	15

#### 7 PIN EBS SOCKET - PART # 600-302



#### 7 PIN (EBS) SOCKET



EBS		
CONTACT/FUNCTION	COLOUR	NO.
Solenoid control valve plus	Red	1
Electronic plus	Black	2
Electronic minus	Yellow	3
Solenoid control valve minus	Brown	4
Warning system	White	5
Data line	White/Green	6
	White/Brown	7

#### **FEATURES**

- 7 Pin socket for EBS braking systems
- Can also be used on 5 Pin applications
- Available with crimp type contacts (OE spec) or screw type contacts

#### 7 PIN ALL FEMALE TRAILER SOCKET - PART # 600-103



7 PIN (ALL FEMALE) SOCKET



- Standard SA 7 Pin socket with all female tube configuration
- · High quality, non-conductive plastic body

#### **EURO/USA METAL SOCKET - PART # 600-502**



#### 7 PIN EURO/USA SOCKET



EUROPEAN STANDARD		
CONTACT/FUNCTION	COLOUR	NO.
Earth/Return/Ground	White	1
Left tail/Number plate	Black	2
Left turn/Hazard	Yellow	3
Stop	Red	4
Right turn/Hazard	Green	5
Right tail/Number plate	Brown	6
Trailer brake control	Blue	7

#### **FEATURES**

- 7 Pin EURO/USA standard socket
- · Heavy duty metal body

#### 13 PIN SOCKET - PART # 600-902



#### **FEATURES**

- 13 Pin European 12 V socket
- · Non-conductive plastic body
- Twist / Lock connection

#### 13 PIN SOCKET



13 PIN EUROPEAN STANDARD		
CONTACT/FUNCTION	COLOUR	NO.
Left turn/Hazard	Yellow	1
Fog tail light	Blue	2
Ground/Earth/Return for contact 1-7	White	3
Right turn/Hazard	Green	4
Right tail/Number plate/Markers	Brown	5
Stop	Red	6
Left tail/Number plate/Markers	Black	7
Reversing lights	Pink	8
Power supply (Continuous plus)	Orange	9
Power supply (Circuited with ignition switch)	Grey	10
Ground for power supply (Circuited with ignition switch)	White/Black	11
NOT OCCUPIED		12
Ground lead for reversing light and power supply (Continuous plus)	White/Red	13

#### U-CONNECT HIGH IMPACT TRAILER SOCKET INCLUDING GROMMET - PART # 600-102-GROMMET

GROMMET



**FRONT** 



#### 7 PIN SOCKET



SOUTH AFRICAN STANDARD		
CONTACT/FUNCTION	COLOUR	NO.
Left turn/Hazard	Yellow	1
Spare	Blue	2
Earth/Return/Ground	White	3
Right turn/Hazard	Green	4
Right tail/Number plate	Brown	5
Stop	Red	6
Left tail/Number plate	Black	7

#### **FEATURES**

- · SA standard 7 Pin socket
- · High quality, non-conductive plastic body

Supplied in kit, with weather-proofing boot

#### 15 PIN / EBS PARK SOCKET - PART # 600-PARK



#### PARK



- Universal parking socket for EBS or 15 Pin
- Used for safe storage of coils when not in use
- · Essential to waterproof coils

#### SA 7 PIN PARK SOCKET - PART # 600-102-PARK





- Parking socket for SA 7 Pin
- Used for safe storage of coils when not in use
- High quality, non-conductive plastic body

Trail-Link specialty products designed for high amp applications, such as battery charging and tail-lift systems as well as military specific purposes.

#### TAILGATE/BATTERY SPIRAL COIL - PART # 100-123



#### **FEATURES**

- · Dual 2 pole bonded cable
- Nominal wire sizes: 2 x 21 mm<sup>2</sup>
- Red = positive; Black = negative

 Nominal AMP rating - 200 A Intermittent / 110 A Continuous

#### 2 POLE PLUG - PART # 500-2POL



- 1 x positive; 1 x negative pole
- · Heavy duty metal body with spring guard
- Nominal AMP rating = 200 A Max

#### 2 POLE SOCKET - PART # 600-2POL



#### **FEATURES**

- 1 x positive; 1 x negative pole
- · Heavy duty metal body with positive latch
- Nominal AMP rating = 200 A Max

#### RECREATIONAL CHARGING COIL (2 X 6 MM) - PART # 100-123-6MM



#### **FEATURES**

- 2 x 6 mm<sup>2</sup> conductors in PUR coil
- Red = positive; Black = negative
- Nominal AMP rating = 50 A

For recreational fridge / battery pack applications

#### 12 PIN MILITARY SPEC PLUG WITH MALE PINS - PART # 500-12P



#### **FEATURES**

- Available on request
- Also available in female tubes (PART# 500-12T)

#### 12 PIN MILITARY SPEC SOCKET WITH FEMALE TUBES - PART # 600-12T







**BACK** 

- Available on request
- Also available in male pins (PART# 600-12P)

#### 2 POLE NATO BOOSTER PLUG - PART # 500-2P50





#### **FEATURES**

- 1 x positive; 1 x negative
- 50 mm<sup>2</sup> contacts
- Nominal AMP rating = 115 A continuous (up to 300 A for 30 seconds)
- · Also available with screw ring

#### 2 POLE NATO BOOSTER SOCKET - PART # 600-2P50





- 1 x positive; 1 x negative
- 50 mm<sup>2</sup> contacts
- Nominal AMP rating = 115 A continuous (up to 300 A for 30 seconds)

# SECTION 6 ANTI-KINK AIR COILS

Trail-Link's High Performance "small-coil" air suzis are manufactured from high quality polyurethane to provide:

- anti-kink
- anti-sag
- excellent memory

#### Other advantages include:

- high flexibility
- superior cold weather operation
- · increased burst pressure

to ensure a longer service life and guaranteed improved performance.

#### **SECTION 6: ANTI-KINK AIR COILS**

#### HIGH PERFORMANCE PUR COIL (YELLOW) - PART # 200-103



#### **FEATURES**

- 5 m nominal working length
- ½ inch BSPT fittings with spring guards
- Temperature range: -40°C to 75°C

#### HIGH PERFORMANCE PUR COIL (RED) - PART # 200-203



- 5 m nominal working length
- ½ inch BSPT fittings with spring guards
- Temperature range: -40°C to 75°C

#### SHORT REACH PUR COIL (YELLOW) - PART # 201-103



#### **FEATURES**

- · Short reach for applications with reduced swing ideal for underslung use behind 5th wheel
- 1/2 inch BSPT fittings with spring guards
- Temperature range: -40°C to 75°C

#### SHORT REACH PUR COIL (RED) - PART # 201-203



- Short reach for applications with reduced swing ideal for underslung use behind 5th wheel
- ½ inch BSPT fittings with spring guards
- Temperature range: -40°C to 75°C

## **SECTION 7 ACCESSORIES**

Trail-Link's accessories have been carefully selected to add safety, convenience and value to towing & towed vehicles, both on the road and off.



#### **UNIVERSAL CATCH ASSEMBLY - PART # 700-102**







#### **FEATURES**

- Provides lock-in of 7 Pin connectors
- Easy installation
- Fits behind existing socket (no need to disconnect wires)
- Registered design
- · Galvanised steel
- Rust resistant

#### SUZI SUSPENSION SPRING - PART # 900-102





- · Assists on low mounting locations
- Supports coils to stay clear of chassis and propshaft
- · Accommodates red, yellow & electrical coils
- · Easy to install

#### **SECTION 7: ACCESSORIES**

#### **BRACKET ASSEMBLY - PART # USK-ASS**



- 2 part assembly for easy installation
- Adjustable angle to protect suzi coils and hoses
- Modular system with add-on and adapter plates
- · Allows for extra connectors and custom configurations
- Registered design

#### KINGPIN LOCK - PART # KPN-LOC-KA



- Theft deterrent
- Prevents unauthorized hooking of trailers
- Unique lock and key combo

### 13 PIN TO 7 PIN ADAPTER - PART # 600-802



### **FEATURES**

- Plug & Play adapter
- · Converts from 13 Pin EURO to 7 Pin SA
- Compatible with VW, Mercedes, Jeep, BMW and Audi etc.

### 7 PIN TO 13 PIN ADAPTER - PART # 600-112



- Plug & Play adapter
- · Converts from 7 Pin SA to 13 Pin EURO

### **SECTION 7: ACCESSORIES**

### **BACKUP ALARM - PART # BUP-ALM**



- 12 V 80 V
- · High decibel output
- For use in safety warning systems eg. reverse buzzer

Trail-Link's new-age LED lights (lights with a difference) possess impressive specifications along with high IP ratings and E-MARK certification.

In addition to the new age technology and excellent quality, they boast spectacular viewing effects.

Our range includes a variety of functional lights and a neon marker light range – never before seen in South Africa.

### CLICK-IN CONNECTOR OPTION AVAILABLE

### **DETAILS**

Many of Trail-Link's LED lights are available with a click-in connector. Here's how it works:



Products with the click-in connector option will have this symbol.









- 7 program settings
- Includes bracket for easy installation (1)
- Multi-voltage
- IP Rating: IP66/IP68

- E-MARK approved
- Also available in red and blue, or with clear lens on request

### FLATPOINT II LED AMBER MARKER - PART # ASP-31-2304-017



CLICK-IN CONNECTOR OPTION





#### **FEATURES**

- Reflector with built-in marker light
- Multi-voltage
- IP Rating: IP69K

- · ADR Zone 2 approved
- E-MARK certification

### FLATPOINT II LED RED MARKER - PART # ASP-31-6404-017



CLICK-IN CONNECTOR OPTION





- · Reflector with built-in marker light
- Multi-voltage
- · IP Rating: IP69K

- · ADR Zone 2 approved
- · E-MARK certification

### FLATPOINT II LED CLEAR MARKER - PART # ASP-31-6904-017



CLICK-IN CONNECTOR OPTION





#### **FEATURES**

- · Reflector with built-in marker light
- Multi-voltage
- IP Rating: IP69K

- · ADR Zone 2 approved
- · E-MARK certification

### 3-IN-1 ROUND COMBINATION LAMP - PART # ASP-COMBO











- 3-in-1 Round Combination Light
- · Tail, Indicator and Stop
- IP Rating: IP69K

- ADR Zone 2 approved
- E-MARK certification
- 4-Way superseal plug and boot included

### RHS SUPERPOINT STALK MARKER LIGHT - PART # ASP-31-3102-017





CLICK-IN CONNECTOR OPTION







#### **FEATURES**

- Multi-voltage
- IP Rating: IP69K
- ADR Zone 2 approved

- E-MARK certification
- · Red. white and amber all in one
- Flexible rubber arm

### LHS SUPERPOINT STALK MARKER LIGHT - PART # ASP-31-3103-017



CLICK-IN CONNECTOR OPTION









- Multi-voltage
- IP Rating: IP69K
- · ADR Zone 2 approved

- E-MARK certification
- · Red, white and amber all in one
- · Flexible rubber arm

### WHITE NEON MARKER ROUND - PART # WAS-782



CLICK-IN CONNECTOR OPTION



#### **FEATURES**

- NEON effect
- Complete with rubber mounting bracket
- Multi-voltage

- IP Rating: IP66/IP68
- E-MARK approved
- Smart polarity connect any wire

### **RED NEON MARKER ROUND - PART # WAS-783**



CLICK-IN CONNECTOR OPTION



- NEON effect
- · Complete with rubber mounting bracket
- Multi-voltage

- IP Rating: IP66/IP68
- · E-MARK approved
- · Smart polarity connect any wire

### AMBER NEON MARKER ROUND - PART # WAS-784



CLICK-IN CONNECTOR OPTION



#### **FEATURES**

- NEON effect
- · Complete with rubber mounting bracket
- · Multi-voltage

- IP Rating: IP66/IP68
- E-MARK approved
- · Smart polarity connect any wire

### NEON STALK MARKER LIGHT RHS - PART # WAS-788P









- NEON effect
- Visibility and improved safety for driver and road users
- · Flexible rubber arm
- Red, white and amber all in one

- · Multi-voltage
- IP Rating: IP66/IP68
- · E-MARK approved
- · Smart Polarity connect any wire

### NEON STALK MARKER LIGHT LHS - PART # WAS-788L









### **FEATURES**

- NEON effect
- Visibility and improved safety for driver and road users
- · Flexible rubber arm
- · Red, white and amber all in one

- Multi-voltage
- IP Rating: IP66/IP68
- · E-MARK approved
- · Smart Polarity connect any wire

### **NUMBER PLATE LIGHT - PART # WAS-244**





- Rugged design
- Multi-voltage
- IP Rating: IP66/IP68

- E-MARK approved
- · Smart polarity connect any wire

### HIGH POWERED LED WORK LIGHT - PART # WAS-684










- Rugged design
- Resistant to high and low temperatures
- High efficiency and output minimum consumption
- With on/off switch (1) and adjustable bracket (2)
- Multi-voltage
- IP Rating: IP66/IP68
- E-MARK approved

## **SECTION 9 UNDERBODY ACCESSORIES**

Trail-Link is a proud manufacturer of electrical harnesses for many OE brands.

Our underbody range includes correctly spec'd trailer cable, protective products and junction boxes for safer wiring.



### 7 CORE TRAILER CABLE - PART # 000-100; 000-101; 000-300



SOUTH AFRICAN STANDARD			
CONTACT/FUNCTION	COLOUR	NO.	
Left turn/Hazard	Yellow	1	
Spare	Blue	2	
Earth/Return/Ground	White	3	
Right turn/Hazard	Green	4	
Right tail/Number plate	Brown	5	
Stop	Red	6	
Left tail/Number plate	Black	7	

### **FEATURES**

- · Correct colour coding
- Extra thick PVC jacket for abrasion resistance
- · Easy to strip
- 6 x 1.5 mm<sup>2</sup> + 1 x 2.5 mm<sup>2</sup> for heavy duty applications (Part # 000-100)
- 6 x 1.0 mm<sup>2</sup> + 1 x 1.5 mm<sup>2</sup> for standard duty applications (Part# 000-101)
- 7 x 0.75 mm<sup>2</sup> for light duty applications (Part # 000-300)

### 15 CORE CABLE - PART # 000-15C



15 PIN EUROPEAN STAN	DARD	
CONTACT/FUNCTION	COLOUR	NO.
Left turn/Hazard	Yellow	1
Right turn/Hazard	Green	2
Fog tail light	Blue	3
Ground/Earth/Return for contact 1-7	White	4
Left tail/Number plate/Markers	Black	5
Right tail/Number plate/Markers	Brown	6
Stop	Red	7
Reversing lights	Pink	8
Power supply (Continuous plus)	Orange	9
Brake lining wear sensor	Grey	10
Pressure sensor for spring brake system	White/Black	11
Rear axle lift system	White/Blue	12
Ground/Earth/Return for data line	White/Red	13
Data line	White/Green	14
Data IIIIc	White/Brown	15

- Correct colour coding
- · Extra thick PVC jacket for abrasion resistance
- Easy to strip

- 12 x 1.5mm<sup>2</sup> + 3 x 2.5mm<sup>2</sup>
- Includes 2 x CAN data lines

### **SECTION 9: UNDERBODY ACCESSORIES**

### 7 CORE EBS CABLE - PART # 000-EBS



EBS			
CONTACT/FUNCTION	COLOUR	NO.	
Solenoid control valve plus	Red	1	
Electronic plus	Black	2	
Electronic minus	Yellow	3	
Solenoid control valve minus	Brown	4	
Warning system	White	5	
Data line	White/Green	6	
	White/Brown	7	

### **FEATURES**

- Correct colour coding
- Extra thick PVC jacket for abrasion resistance
- Easy to strip

- $5 \times 1.5 \text{ mm}^2 + 2 \times 4.0 \text{ mm}^2$
- Includes 2 x CAN data lines

### 5 CORE ABS CABLE - PART # 000-ABS



ABS		
CONTACT/FUNCTION	COLOUR	NO.
Solenoid control valve plus	Red	1
Electronic plus	Black	2
Electronic minus	Yellow	3
Solenoid control valve minus	Brown	4
Warning system	White	5

- Correct colour coding
- Extra thick PVC jacket for abrasion resistance
- Easy to strip
- $3 \times 1.5 \text{ mm}^2 + 2 \times 4.0 \text{ mm}^2$

### 7 PIN ELECTRICAL JUNCTION BOX - PART # JBX-7PIN



### **FEATURES**

- Supplied with fasteners and grommets
- 5 Ports

 Protects electrical connections from the elements

### 10 PIN ELECTRICAL JUNCTION BOX - PART # JBX-10PIN



### **FEATURES**

- Supplied with fasteners and grommets
- 6 Ports

Protects electrical connections from the elements

### **SECTION 9: UNDERBODY ACCESSORIES**

### **CORRUGATED SPLIT SLEEVING**





SIZES AVAILABLE		
ID = 7mm	0D = 10mm	
ID = 10mm	0D = 14mm	
ID = 13mm	0D = 18mm	
ID = 16mm	0D = 20mm	
ID = 20mm	0D = 25mm	

- Underbody wiring and air-hose protection
- Available in 100 m rolls

# SECTION 10 LATEST CONCEPTS

Trail-link's latest "ahead of the game" products.

### **UNDERSLUNG SUZI KIT**

### **DETAILS**

Trail-link's latest "ahead of the game" product is our new underslung suzi kit consisting of:

- 2 x Short-reach air coils (part #201-103 & #201-203)
- 1 x Short reach ebs coil (part #101-903)
- 1 x Mini coil (part #100-703) and
- 2 x Bracket assemblies (part #USK-ASS)





Strategically placed behind kingpin and fifth wheel on interlink trailers, or behind 5th wheel of horse and kingpin of semi trailer configurations, ensuring limited swing on suzis and preventing suzi theft while on the run.



### **How to differentiate the BEST from the rest**

# IT IS TRAILLINK® when...









**Certificate of Authenticity** 

**Proudly South African** 





**Functional bend restrictors** 

Trail-Link printed on moulded plugs



Remember RALLINK doesn't fail.



P.O. Box 880, Silverton, Pretoria Gauteng, South Africa

Tel: +27 (0) 12 335 7402 Fax: +27 (0) 86 635 3286 Email: kim@trail-link.co.za

